

Charm Furniture Polish

Issue number 1, 9 June 2015

## Product Safety Data Sheet

### 1. Product And Company Identification

**Product:** Charm Furniture Polish - 330ml, all variants.

**Manufacturer:** Sanmex International Ltd  
Dalmarnock Road  
Rutherglen  
Glasgow G73 1NY  
United Kingdom

**Phone Number:** 00+44 (0)141 647 2244  
**Fax Number:** 00+44 (0)141 613 1228  
**e mail:** info@sanmex.com

### 2. Hazards Identification

**Symbol:**



**Classification** H222 Danger Extremely Flammable Aerosol  
H229 Pressurised container: May burst if heated.

**Precautionary statements** P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

### 3. Composition/Information on Components

#### Classification according to Regulation (EC) No 1272/2008

Contains:	EINECS Number	CAS Number	% Wt/Wt	Classification
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	918-481-9		5 - 15	Asp. Tox. 1 H304, EUH066, [Flam. Liq. 4 H227], [Skin Irrit. 3 H316 Flammable Gas, Category 1 H220; Gases under pressure H280
n-Butane, Isobutane, Propane mixture	270-704-2	68476-85-7	15 - 30	Ox. Sol. 2 - H272; Acute Tox. 3 - H301; Eye Irrit. 2 - H319; Aquatic Acute 1 - H400
Sodium Nitrite	231-555-9	007632-00-0	Less than 1	

#### Classification according to EU Directive 67/548/EEC / 1999/45 EC

Contains:	EINECS Number	CAS Number	% Wt/Wt	Classification
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	918-481-9		5 - 15	Xn, R65, R68
n-Butane, Isobutane, Propane mixture	270-704-2	68476-85-7	15 - 30	F+; R12
Sodium Nitrite	231-555-9	007632-00-0	Less than 1	O, T, N; R8, R25, R50

Also contains Fragrance.

Charm Furniture Polish

Issue number 1, 9 June 2015

**4. First-Aid Measures**

**Eyes:** Rinse with water for 15 minutes.  
**Skin:** Wash with soap and water.  
**Inhalation:** Remove the person to fresh air. If breathing has stopped administer artificial respiration. Obtain medical attention.  
**Ingestion:** Wash out mouth with water. Do not induce vomiting. Give water to drink. Seek medical attention.

**5. Fire-Fighting Measures**

Use foam, carbon dioxide or dry powder extinguishers.

**6. Accidental Release Measures**

Absorb with any inert material. Ensure adequate ventilation. Remove sources of ignition.

**7. Handling and Storage**

Keep away from sources of ignition. Do not smoke while using. Keep at temperature not exceeding 50°C. Protect from sunlight. Keep out of the reach of children. Intentional misuse by deliberately inhaling the contents can be harmful or fatal.

**8. Exposure Controls/Personal Protection**

Use only as directed on the can. Avoid contact with the skin and eyes.

**9. Physical and Chemical Properties**

**Appearance:** Pale yellow Liquid  
**Odour:** As fragrance  
**pH:** 6.0 - 8.0

**10. Stability and Reactivity**

As with all aerosol cans, protect from sunlight and do not expose to temperatures exceeding 50°C.

**11. Toxicological Information**

**Eyes:** May cause irritation.  
**Skin:** May irritate sensitive skin.  
**Ingestion:** May cause nausea and vomiting.  
**Inhalation:** May cause dizziness, stupor or unconsciousness depending on the extent of exposure.

**12. Ecological Information**

Not expected to cause significant environmental impact.

**13. Disposal Considerations**

Do not pierce or burn even after use. Dispose according to national and local authority guidelines.

Cham Furniture Polish

Issue number 1, 9 June 2015

14. Transport Information

Transport Type	ADR (Road/Rail)	SEA	AIR
UN Number	UN 1950	UN 1950	UN 1950
Class	2.1	2.1	2.1
Proper shipping name	Aerosols	Aerosols	Aerosols, flammable
Packing group	None	None	None
Marine pollutant	N/A	No	N/A
Other information	'Limited quantity' provisions apply. No Tremcard required.	'Limited quantity' provisions apply.	'Limited quantity' provisions apply. Hazard label required: Flammable Gas.

15. Regulatory Information

Symbol:



Classification	H222 Danger Extremely Flammable Aerosol H229 Pressurised container: May burst if heated.
Precautionary statements	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

16. Other information

R phrases used in this document

R8 Contact with combustible material may cause fire	H220 Extremely flammable gas.
R12 Extremely Flammable	H227 Combustible liquid
R25 Toxic if swallowed	H272 May intensify fire; oxidiser
R50 Very toxic to aquatic organisms	H280 Contains gas under pressure; may explode if heated.
R65 Harmful: may cause lung damage if swallowed.	H301 Toxic if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.	H304 May be fatal if swallowed and enters airways
	H316 Causes mild skin irritation
	H319 Causes serious eye irritation.
	H400 Very toxic to aquatic life.

This Safety Data does not constitute the users own assessment of workplace risk.